Ralston Instruments

NPAK-2FBA-6-3

Nitropak, 1/4" female NPT gauge adapter, 6ft, 3ft hoses, (2) 1/4" MNPT process connections

Self contained nitrogen source includes all connections and hoses to connect directly to a pressure gauge or calibrator

Features

- · Proprietary pressure balanced fine adjustment piston allows for extremely precise, finger-tip control of pressure at 0.03 psi (2 mbar) or 3000 psi (210 bar) or any range in between.
- · Easily refillable nitrogen cylinder holds enough gas for multiple calibrations
- · Nylon bag to hold hose and fittings attached to inside of lid
- Includes storage compartment in control panel for pressure reference test gauge
- · Low volume Quick-test hose, gauge adapter and process connection can be attached to NPAK without thread sealant or a wrench
- Designed to meet US Department of Transportation (DOT) and Canadian Transport Canada (TC) standards
- CE Approved for use in European Union Designed to meet Pressure Equipment Directive (PED) and Transportable Pressure Equipment (TPED) standards
- · Made in USA





4300 Stine Road, Suite 203, Bakersfield, CA 93313-2352 Phone (661) 398-2105 Fax (661)832-6454 e-mail: tom@cencalinst.com website: www.cencalinst.com

Item Includes

- · Assembly NPAK Assembly (NPAK)
- Gauge Adapter 1/4" female NPT x female Quick-test, no check-valve, brass (QTHA-2FBA)
- Hose Quick-test 6900 psi hose, brass hose ends, 6 ft (1.83 m) long (QTQT-HOS-6ft)
- Hose Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Hose Adapter 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose Adapter 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)

Specifications

Pressure Range	0 to 3000 psi (0 to 207 bar)
Vacuum Range	0 to 10"Hg (0 to 254 mmHG)
Temperature range	0 to 130 °F (-18 to 54 °C)
Construction	ABS Plastic, Aluminum, Anodized Aluminum, Brass, Plated Steel, Stainless Steel, Zippered Nylon with Velcro
Seal materials	Buna-N, Delrin, Teflon

